

PROBAU Tile Adhesive PFK

The batch number can be found on the side of the sack or on the delivery note.

DECLARATION OF PERFORMANCE

Number of the Declaration of Performance and unique identification code of the product type
QUICK-101027-01-EN12004-C1T

Intended use
Cement-based mortar for ceramic tiles and slabs on walls and floors, both indoors and outdoors.

Manufacturer
quick-mix Gruppe GmbH & Co. KG Mühleneschweg 6 49090 Osnabrück Germany

System of assessment and verification of constancy of performance of the product
System 4 for behaviour in fire, System 3 for all other essential characteristics

The notified body
Materialprüfungsamt Nordrhein-Westfalen e.V. (Materials Testing Institute in North Rhine-Westphalia) - ID number 0432 has carried out initial type testing of the product with regard to the essential characteristics (except for behaviour in fire) under System 3 and certified the following:

Harmonised standard
EN 12004 :2012

Declared performance

Essential characteristics	Performance
Behaviour in fire	A1
Bond strength	Tensile bond strength after exposure to dry conditions: $\geq 0.5 \text{ N/mm}^2$
Durability with regard to the effects of exposure to weather and heat	Tensile bond strength after exposure to heat: $\geq 0.5 \text{ N/mm}^2$
Durability with regard to the effects of exposure to weather and heat	Tensile bond strength after immersion in water: $\geq 0.5 \text{ N/mm}^2$
Durability with regard to the effects of freeze-thaw cycles	Tensile bond strength after freeze-thaw exposure: $\geq 0.5 \text{ N/mm}^2$
Release of hazardous substances	NPD

The performance of the product described above corresponds to the declared performance. The above-mentioned manufacturer alone is responsible for the preparation of the declaration of performance in line with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Dr. Martin Kanig, Research & Development
(Name and position)

Osnabrück, 4 January 2016
(Place and date of issue)


(Signature)