## PROBAU Flexible Adhesive PFKX

The batch number can be found on the side of the sack or on the delivery note.

## **DECLARATION OF PERFORMANCE**

Number of the Declaration of Performance and unique identification code of the product type QUICK-101106-01-EN12004-C2TES1

Intended use

The flexible adhesive is a versatile construction adhesive with very high adhesive strength and elasticity.

Manufacturer

quick-mix Gruppe GmbH & Co. KG Mühleneschweg 6 49090 Osnabrück Germany

System of assessment and verification of constancy of performance of the product System 4 for behaviour in fire, System 3 for all other essential characteristics

The notified body

Materialprüfungsamt Nordrhein-Westfalen e.V. (Materials Testing Institute in North Rhine-Westphalia) - ID number 0432 has carried out initial type testing of the product with regard to the essential characteristics (except for behaviour in fire) under System 3 and certified the following:

Harmonised standard EN 12004 :2012

Declared performance

Essential characteristics	Performance
Behaviour in fire	E
Bond strength	Tensile bond strength after exposure to dry conditions: ≥ 1.0 N/mm²
Durability with regard to the effects of exposure to weather and heat	Tensile bond strength after exposure to heat: ≥ 1.0 N/mm²
Durability with regard to the effects of exposure to weather and heat	Tensile bond strength after immersion in water: ≥ 1.0 N/mm²
Durability with regard to the effects of exposure to freeze-thaw cycles	Tensile bond strength after freeze-thaw exposure: ≥ 1.0 N/mm²
Release of hazardous substances	NPD

The performance of the product described above corresponds to the declared performance. The above-mentioned manufacturer alone is responsible for the preparation of the declaration of performance in line with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

<u>Dr. Michael Fooken, Research & Development</u>
(Name and position)

Osnabrück, 10 July 2017

(Place and date of issue)

Michael Fooken (Signature)