

Shower Sealant

Types of application:

PROBAU Shower Sealant is a solvent-free, ready-to-use sealing compound that can be applied with a brush, roller or trowel. Once hardened, the shower sealant is impermeable to water and compatible with silicone. It is odour-free during processing and dries quickly. The sealant is used to professionally seal surfaces beneath tiling and paving in bathrooms and damp rooms. It is applied on the side that is exposed to water.

Technical data:

Processing temperature: at least + 5 °C
Thickness of dried layer: 0.8 mm
Thickness of wet layer: 1.1 mm

Subsurface:

The subsurface must be sound, load-bearing, even and free of oil, grease, dust and through cracks. Pretreat absorbent subsurfaces (using shower sealant diluted 1:1 with water). Uneven surfaces must be levelled using PROBAU Concrete and Restoration Filler before you apply the sealant.

Processing and application:

Stir the PROBAU Shower Sealant thoroughly before use. Then apply two or three thick, even coats of the sealant using a synthetic or lambs wool roller, paintbrush or broad brush. Each coat must be allowed to dry before the next coat is applied. In areas that are susceptible to cracking, such as corners, wall-floor junctions, pipe penetrations etc., it is advisable to incorporate PROBAU Shower Sealing Strips and/or PROBAU Pipe Penetration Collars. After the PROBAU Shower Sealant has been allowed to dry for approximately 2 hours, ceramic tiles can be laid on top of it using PROBAU Flexible Adhesive.

Notes regarding subsequent works:

After the shower sealant has been allowed to dry for approximately 2 hours, ceramic tiles can be laid on top of it using flexible adhesive.

Cleaning the tools:

Remove any stains and clean the tools with water immediately after use.

Drying period:

At + 20 °C and a relative air humidity of 50 %, the drying period is approximately 2 hours.

Quantity required:

Depending on the properties of the subsurface, the quantity required is approximately 1 to 2 kg/m² (assuming that 2 or 3 coats are applied).

Storage:

Store appropriately in dry conditions.

Packaging:

4-kg pail

Note:

The technical details are valid at 20 °C and 50 % relative humidity.

Observe the safety instructions on the packaging.

Shower Sealant

The information provided is based on extensive tests and practical experience. It does not apply to every application situation. For this reason we recommend that you carry out a trial if necessary. Subject to technical alterations within the framework of further development. Our general terms and conditions apply.

Further information is available from:
Service Hotline: 0049 (0) 180/3 000 462

BAHAG AG
Postfach 100561
D-68005 Mannheim

BAUHAUS SCHWEIZ AG
Sägetstrasse 5
CH-3123 Belp / Bern

BAHAG AG
Postfach 4000
A-4600 Wels

BAUHAUS ZAGREB k.d.
Škorpi Kora 27
HR-10000 Zagreb