

## Special Sealant for Walls + Floors

### Types of application:

Sealing mortar and bonding bridge for use beneath PROBAU Stone Carpet. For walls and floors, indoors and outdoors. Particularly for use in damp and wet rooms. For use as a bonding bridge on non-absorbent subsurfaces (e.g. on existing tiles).

### Subsurface:

The subsurface must be sound, load-bearing, dry and free of dust and other adhesion inhibiting substances. In the case of non-absorbent subsurfaces (such as existing tiles or smooth-formed concrete), apply a scratch coat of PROBAU Special Sealant first, using a smoothing trowel to create a rough, scraped finish.

This will ensure good bonding. Highly absorbent subsurfaces must be prewetted. Uneven subsurfaces must be levelled in advance.

### Processing and application:

Pour approximately 1.8 l of clean water into a clean container. Then add the contents of the sack (6 kg) and mix using a power mixer set at a low speed until you have a lump-free, paste-like mortar. When using as a sealant, 2 layers need to be applied using a heavy-duty paint brush or smoothing trowel. The first layer must be allowed to dry for at least 8 hours. The total layer thickness must be at least 2 mm. Allow the sealant to dry thoroughly for approximately 2 to 3 days before applying the PROBAU Stone Carpet. Protect the fresh sealant from moisture until it has completely hardened. If the subsurface is non-absorbent, apply a scratch coat of PROBAU Stone Carpet Primer using a smoothing trowel to create a rough, scratched contact layer.

Do not process at air material and subsurface temperatures below +5 °C or above + 30 °C.

### Quantity required:

As a sealant: 6 kg of PROBAU Special Sealant is sufficient for approximately 1.75 m².

### Storage:

Store appropriately in dry conditions.

### Packaging:

6-kg bag



The information provided is based on extensive tests and practical experience. It does not apply to every application situation. For this reason we recommend that you carry out a trial if necessary. Subject to technical alterations within the framework of further development. Our general terms and conditions apply.

Further information is available from:  
Service Hotline: 0049 (0) 180/3 000 462

BAHAG AG  
Postfach 100561  
D-68005 Mannheim

BAUHAUS SCHWEIZ AG  
Sägetstrasse 5  
CH-3123 Belp / Bern

BAHAG AG  
Postfach 4000  
A-4600 Wels

BAUHAUS ZAGREB k.d.  
Škorpi Kora 27  
HR-10000 Zagreb