

Extra Adhesive plus 200ml

High-quality, solvent-free acrylic emulsion adhesive for indoor use.

Type of use:

PROBAU Extra Adhesive plus is used for fixing skirting boards, gypsum, chipboard, gypsum plasterboard, polystyrene panels and fibre cement panels.

Application:

1. Pull off the end cap.
2. Break off the securing lug.
3. Set the desired pressure by turning the dispensing head towards the MAX setting.
4. Press the application lever to squeeze out the material.
5. After use, turn the head back towards the MIN setting. Remove any product residue from the nozzle tip and then replace the end cap.

Apply the adhesive in dots or beads of uniform thickness. Always apply adhesive at the corner points and along the edges. When bonding surfaces, apply the adhesive in a thin, even layer on one side, using a notched spreader, for example. Position the material immediately and pressed firmly or tap into place. Provide support or temporary fixings if necessary. Low temperatures and wet subsurfaces delay the hardening process. Due to the great variety of possible applications, preliminary trials should always be carried out. Remove any excess adhesive immediately. Once the adhesive has hardened, it can only be removed mechanically. The same applies to tools.

Subsurface:

Dust, loose material, wallpaper, grease, wax and non-bonded paint or varnish coatings must be thoroughly removed from the subsurface/bonding surfaces. Smooth subsurfaces must be roughened, and highly absorbent subsurfaces, such as plaster, concrete, aerated concrete etc., must be pretreated with a mixture of adhesive and water in a 1 to 5 ratio.

Notes: If the adhesive is to harden properly, either the subsurface or the material to be bonded must be absorbent. Bonding-resistant plastics such as polyethylene, Teflon and bitumen-bound subsurfaces are not suitable as bonding surfaces.

Processing temperature:

+5 °C to +40 °C (optimally +5 °C to +20 °C).

Temperature resistance:

Approximately -20 °C to +80 °C.

Maximum final strength:

After approximately 72 hours

Initial adhesive strength:

Approximately 150 kg/m²

Behaviour in fire:

Class E

Standards and tests:

GEV Emicode EC 1plus



Extra Adhesive plus 200ml

Further information on the declaration of performance can be found at www.probau.eu

Storage:

Store in cool, dry, frost-free conditions.

Shelf life:

In its unopened original packaging, the product has a shelf life of 18 months from its date of manufacture. See the date stamp.

Container:

200ml pressure pack

Colours:

White

Disposal:

Only send completely empty packaging for recycling. Leftover material can be disposed of at your local disposal centre for problem waste. AVV waste code number 080410.

Constituents:

May contain traces of isothiazolinones. May produce an allergic reaction. Advisory service hotline: +49 541 601-601. A safety data sheet is available on enquiry.

Precautionary statements:

The container is pressurised: it can burst when heated up. If medical advice is needed, show the product packaging or identification label to the doctor. Read the identification label before using the product. Keep the product away from hot surfaces, sparks, open flames and other sources of ignition. No smoking. Never pierce or burn, even when empty. Protect from direct sunlight. Do not expose to temperatures above 50 °C/122 °F. Keep out of the reach of children. A safety data sheet is available on enquiry.

Notes:

We accept no liability for errors relating to faulty use or any consequences thereof. Observe the instructions on the packaging.

The information provided is based on extensive tests and practical experience. It does not apply to every application situation. For this reason, we recommend that you carry out a trial if necessary. Subject to technical alterations within the framework of further development. Our general terms and conditions apply.

Further information is available from:
Service Hotline: 0049 (0) 180/3 000 462

BAHAG AG
Postfach 100561
D-68005 Mannheim

BAUHAUS SCHWEIZ AG
Sägetstrasse 5
CH-3123 Belp / Bern

BAHAG AG
Postfach 4000
A-4600 Wels

BAUHAUS ZAGREB k.d.
Škorpi Kora 27
HR-10000 Zagreb