

# Declaration of Performance

according to CPR 305/2011/EU




DoP-Nr.: 114330-14-0025

1. Unique identification code of the product-type:	CD-ceiling profile										
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Art. 11(4):	See packing/label of the product and table Annex 1										
3. Intended use or uses of the product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Metal section for substructure of sheets of drywall EN 14195										
4. Name, registered trade name and contact address of the manufacturer as required pursuant to Article 11 (5):	BAHAG AG Gutenbergstr. 21 68167 Mannheim, Germany										
5. Name and contact address of the authorised representative whose mandate covers the tasks specified article 12 (2):	not applicable										
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	System 4										
7. In case of declaration of performance concerning a construction product covered by a harmonised standard:  Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant):	Factory owned production controlle and initial testing by producer										
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	not applicable										
9. Declared performance:											
<table border="1"><thead><tr><th>Essential characteristics</th><th>Performance</th><th>Harmonised technical specification</th></tr></thead><tbody><tr><td>Reaction to fire</td><td>Class A1</td><td rowspan="3">EN 14195</td></tr><tr><td>Yield strength</td><td>240 N/mm<sup>2</sup></td></tr><tr><td>Hazardous substances</td><td>NPD</td></tr></tbody></table>		Essential characteristics	Performance	Harmonised technical specification	Reaction to fire	Class A1	EN 14195	Yield strength	240 N/mm <sup>2</sup>	Hazardous substances	NPD
Essential characteristics	Performance	Harmonised technical specification									
Reaction to fire	Class A1	EN 14195									
Yield strength	240 N/mm <sup>2</sup>										
Hazardous substances	NPD										
10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration is issued under the sole responsibility of the manufacturer identified in point 4.											

Mannheim, 21.10.2014

  
Kim Herrmann  
Head marketing construction material

  
Daniel Fleer  
Bereichsleiter Qualitätssicherung

**Anhang 1 - Produktübersicht für die Leistungserklärung DoP-Nr.**

**114330-14-0025**

**Annex 1 - product overview for the Declaration of Performance DoP-Nr.**

[illegible]