

PROBAU Polymer Bond + Seal PLUS PPKD 450
Grey and White

The batch number can be found on the side of the sack or on the delivery note.

DECLARATION OF PERFORMANCE

Number of the Declaration of Performance

QUICK-110113-02-EN15651-1

Unique identification code of the product type

EN 15651-1:FEXT-INT

Intended use

Joint sealants for façade elements, for interior and exterior use

Manufacturer

quick-mix Gruppe GmbH & Co. KG • Mühleneschweg 6 • 49090 Osnabrück • Germany

System of assessment and verification of constancy of performance of the product

System 3 for behaviour in fire

The notified body

The notified body, SKZ Tecona GmbH, ID number 1213, has determined the product type and the behaviour in fire by carrying out type testing according to System 3 and has issued corresponding test and classification reports.

Declared performance

Conditioning:

Method A

Substrate:

Glass, aluminium.

Essential characteristics	DIN EN 15651-1 Façade elements F-EXT-INT
Behaviour in fire	Class E
Release of substances that are harmful to health and/or to the environment.	NPD
Stability under load	≤ 3 mm
Volume loss	≤ 25 %
Tensile properties (i.e. expansion behaviour) at break (at 23°C)	> 25%
Durability	Passed

The performance of the product described above corresponds to the declared performance. The above-mentioned manufacturer alone is responsible for the preparation of the declaration of performance in line with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer by:

Dr. Michael Fooker, Research & Development Manager

(Name and position)

Osnabrück, 13 June 2017

(Place and date of issue)



(Signature)