

## Grout Colour

### Types of application:

Grout Colour is used to revitalise the appearance or to change the colour of unsightly grouting between glazed ceramic tiles in indoor areas. For walls and floors.



### Material:

This acrylic copolymer grout colour is solvent-free, low in pollutants, eco-friendly, stain resistant and water repellent and has a matt finish when dry. It is resistant to alkaline substrates and to non-abrasive detergents, such as soap and shampoo, and prevents the growth of mould and fungi.

### Subsurface:

The grout must be sound, load-bearing and free of dust, dirt, oil, grease and loose material. Soft, crumbling or damaged grout must be scraped out and replaced. Grout that is greasy or is covered in fungi or dirt must first be cleaned thoroughly using a sponge and household detergent. Any lime residues must be removed. Rinse the cleaned surfaces with plenty of clean water and allow them to dry.

### Quantity required:

The quantity required depends on the tile format and the width of the joints. 250 ml is sufficient for approximately 10 to 15 m<sup>2</sup>.

### Processing and application:

Stir the grout colour thoroughly before use and then apply thickly and evenly. Only use the special brush that is provided. The grout colour should extend beyond the edges of the joints by approximately 1 to 2 mm. After approximately 60 minutes, wet the entire tiled area a little and then wait about 5 minutes. The excess grout colour will have swollen somewhat after being wetted and can now be removed from the surface of the tiles using the hard side of the sponge, wiping diagonally or circularly until the edges of the joints have a clear and sharp appearance again. Then immediately clean the entire surface again with an almost dry sponge (soft side) and allow to dry.

Final cleaning can take place after a drying period of several hours. In showers, the grout colour should be allowed to dry for at least two days before the shower is used again.

Do not carry out works at air, material and surface temperatures below + 5 °C or above + 25 °C.

### Storage:

Store appropriately in dry conditions.

### Packaging:

White:	250-ml package
Grey:	250-ml package
Beige:	250-ml package

## Grout Colour

**Note:**

The technical details are valid at 20 °C and 65 % relative humidity. Observe the safety instructions on the packaging.

The information provided is based on extensive tests and practical experience. It does not apply to every application situation. For this reason we recommend that you carry out a trial if necessary. Subject to technical alterations within the framework of further development. Our general terms and conditions apply.

Further information is available from:  
Service Hotline: 0049 (0) 180/3 000 462

**BAHAG AG**  
Postfach 100561  
D-68005 Mannheim

**BAUHAUS SCHWEIZ AG**  
Sägetstrasse 5  
CH-3123 Belp / Bern

**BAHAG AG**  
Postfach 4000  
A-4600 Wels

**BAUHAUS ZAGREB k.d.**  
Škorpi Kora 27  
HR-10000 Zagreb