

## Cement Film Remover

Specially prepared cleaning agent for the removal of lime and cement films on concrete and masonry surfaces.

### Type of use:

The cement film remover easily removes the efflorescence and leaching that often arises unavoidably on masonry and concrete surfaces. Light soiling can also be removed.

### Material:

The cement film remover is a clear, low-odour liquid.

### Processing and application:

The cement film remover is ready to use and need not be diluted. The soiled masonry or concrete surface must be thoroughly pre-wetted. The film remover can then be sprayed onto the soiled surface using a garden sprayer or fruit tree sprayer. The light-coloured areas start to “foam” when the spray is applied. The effect of the cement film remover can be intensified by mechanical cleaning (using a scrubbing brush, for example). Several applications may be necessary to remove all traces of soiling.

Before it has a chance to dry, the cement film remover must be removed from the cleaned surface by rinsing from top to bottom with plenty of water.

### Quantity required:

The quantity required depends on the amount of soiling and the absorbency of the subsurface. Depending on how the cement film remover is applied, approximately 100 to 150 ml are required per square metre.

### Storage:

The cement film remover must be stored in frost-free conditions. If the cement film remover has been stored for a longer period in its closed container, it should be stirred well before use.

### Declaration of constituents in accordance with EC recommendation:

5 to 15 % inorganic acids, < 5 % non-ionic surfactants, organic acids, fragrances. Contains hydrochloric acid.

### Packaging:

1-litre bottle  
5-litre canister

### Please note:

Eyes and hands must always be protected when working with the cement film remover. Splashes on clothing must be washed off immediately using clean water.

All surfaces that are not made of concrete, precast concrete units, exposed aggregate slabs, plaster, screed, tiles or other ceramic materials must be covered for protection.

### Note:

Observe the safety instructions on the packaging.



## Cement Film Remover

The information provided is based on extensive tests and practical experience. It does not apply to every application situation. For this reason we recommend that you carry out a trial if necessary. Subject to technical alterations within the framework of further development. Our general terms and conditions apply.

Further information is available from:  
Service Hotline: 0049 (0) 180/3 000 462

**BAHAG AG**  
Postfach 100561  
D-68005 Mannheim

**BAUHAUS SCHWEIZ AG**  
Sägetstrasse 5  
CH-3123 Belp / Bern

**BAHAG AG**  
Postfach 4000  
A-4600 Wels

**BAUHAUS ZAGREB k.d.**  
Škorpi Kora 27  
HR-10000 Zagreb