

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

**1 Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: Probau Silikon-Entferner**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
SU21 Consumer uses: Private households / general public / consumers  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Organic solvent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
quick-mix Gruppe GmbH & Co.KG  
Mühlenschweg 6  
49090 Osnabrück  
  
Tel.: +49(0)541/60101  
Fax.: +49(0)541/601853  
Email: info@quick-mix.de
- **Further information obtainable from:** Abteilung Produktsicherheit
- **1.4 Emergency telephone number:**  
Giftinformationszentrum Nord  
+49 (0) 551/19240

**2 Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1      H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3      H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

Trade name: Probau Silikon-Entferner

(Contd. of page 1)

### Hazard pictograms



GHS02 GHS07 GHS08

### Signal word Danger

### Hazard-determining components of labelling:

Hydrocarbones, C9-C10, n-Alkane, l-Alkane, cyclics, &lt; 2% aromatics

### Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves / eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3 Other hazards

### Results of PBT and vPvB assessment

- PBT: Not applicable.

- vPvB: Not applicable.

## 3 Composition/information on ingredients

### 3.2 Mixtures

- Description: Mixture of substances listed below with nonhazardous additions.

### Dangerous components:

EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbones, C9-C10, n-Alkane, l-Alkane, cyclics, < 2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412	50-<100%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	10-30%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

## 4 First aid measures

### 4.1 Description of first aid measures

#### General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Do not leave affected persons unattended.

Personal protection for the First Aider.

#### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

Trade name: Probau Silikon-Entferner

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
If swallowed or in case of vomiting, danger of entering the lungs.

### 5 Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Ensure adequate ventilation  
Keep away from ignition sources.  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.  
Keep away from heat and direct sunlight.  
Take note of emission threshold.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store only in the original receptacle.  
Provide solvent resistant, sealed floor.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

Trade name: Probau Silikon-Entferner

(Contd. of page 3)

- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**  
Store under lock and key and out of the reach of children.  
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

#### · Ingredients with limit values that require monitoring at the workplace:

##### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
	Sk

#### · DNELs

##### Hydrocarbones, C9-C10, n-Alkane, l-Alkane, cyclics, < 2% aromatics

Oral	long-term, systemic effects	300 mg/kg/d (Ver)
Dermal	long-term systemic effects	300 mg/kg bw/d (Ver)
		300 mg/kg bw/d (workers)
Inhalative	long-term systemic effects	900 mg/m <sup>3</sup> (Ver)
		1500 mg/m <sup>3</sup> (workers)

##### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	long-term, systemic effects	1.67 mg/kg/d (Ver)
Dermal	long-term systemic effects	153.5 mg/kg bw/d (Arb)
		54.8 mg/kg bw/d (Ver)
Inhalative	long-term systemic effects	275 mg/m <sup>3</sup> (Arb)
		33 mg/m <sup>3</sup> (Ver)

#### · PNECs

##### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

environment, aquatic compartment	0.0635 mg/l (Mee)
	0.635 mg/l (Süß)
environment, aquatic compartment, intermittent	0.329 mg/kg bw/d (Mee)
	3.29 mg/kg bw/d (Süß)
environment, waste water treatment plant	100 mg/l (Abw)
environment, sediment	0.29 mg/kg dry weight (Bod)

- **Additional information:** The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

##### · Personal protective equipment:

##### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.

##### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

**Trade name: Probau Silikon-Entferner**

(Contd. of page 4)

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Fluorocarbon rubber (Viton)

- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Solvent resistant protective clothing

## 9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Colourless
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	137 °C (DIN 51751)

- **Flash point:** >23 °C (DIN 51755 geschl. Träger)

- **Flammability (solid, gas):** Not applicable.

- **Ignition temperature:** 315 °C (ASTME E-659)

- **Decomposition temperature:** Not determined.

- **Auto-ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

Trade name: Probau Silikon-Entferner

(Contd. of page 5)

· <b>Explosion limits:</b>	
<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	10.8 Vol %
· <b>Vapour pressure at 20 °C:</b>	5 hPa
· <b>Density at 20 °C:</b>	0.78 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	100.0 %
<b>VOC (EC)</b>	100.00 %
· <b>9.2 Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**  
Forms explosive gases/fumes.  
Used empty containers may contain product gases which form explosive mixtures with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

### Hydrocarbones, C9-C10, n-Alkane, l-Alkane, cyclics, < 2% aromatics

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	>4951 mg/l (rat)

### CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

**Trade name: Probau Silikon-Entferner**

(Contd. of page 6)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.


## 12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** Moderately /partly biodegradable
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>14.1 UN-Number</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>   | UN1263  |
| <ul style="list-style-type: none"> <li>· <b>14.2 UN proper shipping name</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>  | 1263 PAINT RELATED MATERIAL, special provision 640E<br>PAINT RELATED MATERIAL |
| <ul style="list-style-type: none"> <li>· <b>14.3 Transport hazard class(es)</b></li> <li>· <b>ADR, IMDG, IATA</b></li> </ul>  |   |
| <div style="text-align: center;">  </div> <ul style="list-style-type: none"> <li>· <b>Class</b></li> </ul> | 3 Flammable liquids.  |

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

Trade name: Probau Silikon-Entferner

(Contd. of page 7)

· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S</u> -E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640E, 3, III

### 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Information about limitation of use:**  
Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.
- **Other regulations, limitations and prohibitive regulations**  
VOC-Gehalt:  
Produktunterkategorie B/a, VOC-Grenzwert 850 g/L (gem. RL 2004/42/EG, Anhang II)  
Dieses Produkt enthält max. 778 g/L
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 9)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.03.2017

Version number 5

Revision: 22.03.2017

**Trade name: Probau Silikon-Entferner**

(Contd. of page 8)

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Abteilung Produktsicherheit

· **Abbreviations and acronyms:**

- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the previous version altered.**

GB