

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name : PROBAU Schnellzement
UFI : JK23-G0YV-300T-2XCG

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Intended for general public
Use of the substance/mixture : mineral dry mortar for mixing with water
Use of the substance/mixture : Building and construction work

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer/Supplier**

Sievert Baustoffe GmbH & Co. KG
Mühlenschweg 6
D-49090 Osnabrück
T +49 541 601-01 - F +49 541 601-853

Informing department

Abteilung: Technische Beratung
T +49 541 601-01
info@sievert.de

Email competent person

info@sievert.de

1.4. Emergency telephone number

Emergency number : National Health Service (NHS)
24 hour national number consumer
England and Scotland: 111
Wales: 0845 46 47
Northern Ireland: call your local General Practitioner

Call 999 if there is a life-threatening incident.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 1 H318
Specific target organ toxicity — Single exposure, Category 3, H335
Respiratory tract irritation
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes serious eye damage. Causes skin irritation. May cause respiratory irritation.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) :

Danger

Contains :

Cement, portland, chemicals; calcium dihydroxide

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Hazard statements (CLP)	: H315 - Causes skin irritation. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P261 - Avoid breathing dust, fume. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P310 - Immediately call a POISON CENTER, a doctor. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 - If skin irritation occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Quartz (SiO ₂) substance with a Community workplace exposure limit	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	50 – 100	Not classified
Cement, portland, chemicals	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4	25 – 50	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
calcium dihydroxide	(CAS-No.) 1305-62-0 (EC-No.) 215-137-3 (REACH-no) 01-2119475151-45-xxxx	≤ 2.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : None known. The product is not flammable.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust, mist.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.
Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Avoid breathing dust, fume.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry protected location to prevent any moisture contact. Store in a well-ventilated place. Product must only be kept in the original packaging. Refer to the recommendations of the supplier.
Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

No additional information available

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cement, portland, chemicals (65997-15-1)	
United Kingdom - Occupational Exposure Limits	
Local name	Portland cement
WEL TWA (mg/m ³)	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

calcium dihydroxide (1305-62-0)	
EU - Occupational Exposure Limits	
Local name	Calcium dihydroxide
IOELV TWA (mg/m ³)	1 mg/m ³ (Respirable fraction)
IOELV STEL (mg/m ³)	4 mg/m ³ (Respirable fraction)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom - Occupational Exposure Limits	
Local name	Calcium hydroxide
WEL TWA (mg/m ³)	1 mg/m ³ Respirable fraction 5 mg/m ³
WEL STEL (mg/m ³)	4 mg/m ³ Respirable fraction
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Quartz (SiO₂) (14808-60-7)	
EU - Occupational Exposure Limits	
Local name	Silica crystalline (Quartz)
IOELV TWA (mg/m ³)	0.05 mg/m ³ (respirable dust)
Notes	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

Hand protection:

Chemically resistant protective gloves. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Wear closed safety glasses. EN 166. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure

Skin and body protection:

Wear suitable protective clothing. EN ISO 13688

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Dust formation: dust mask. P2. EN 143. Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product. The above mentioned instructions regarding the protective equipment refer to the industrial use of larger quantities.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: Grey.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: Not applicable
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: > 999 °C
Flash point	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: Not applicable
Relative vapour density at 20 °C	: Not applicable
Relative density	: No data available
Solubility	: Water: of very low solubility
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Acids.

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (No data available)
Acute toxicity (dermal) : Not classified (No data available)
Acute toxicity (inhalation) : Not classified (No data available)

calcium dihydroxide (1305-62-0)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 425 method)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402 method)
LC50 Inhalation - Rat (Dust/Mist)	> 6.04 mg/l/4h (OECD 436 method)

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Potential adverse human health effects and symptoms : May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.
Hazardous to the aquatic environment, short-term (acute) : Not classified (No data available)
Hazardous to the aquatic environment, long-term (chronic) : Not classified (No data available)

calcium dihydroxide (1305-62-0)	
LC50 fish 1	50.6 mg/l (96 h; Oncorhynchus mykiss; (OECD 203 method))
EC50 Daphnia 1	49.1 mg/l (48 h; Daphnia magna; (OECD 202 method))
ErC50 (algae)	48 mg/l (72 h; Pseudokirchneriella subcapitata; (OECD 201 method))
NOEC chronic crustacea	32 mg/l (14 d; Crangon septemspinosa)
NOEC chronic algae	48 mg/l (72 h; Pseudokirchneriella subcapitata; (OECD 201 method))

12.2. Persistence and degradability

calcium dihydroxide (1305-62-0)	
Persistence and degradability	Not applicable for inorganic substances.

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Quartz (SiO ₂) (14808-60-7)	
Persistence and degradability	Not applicable for inorganic substances.

12.3. Bioaccumulative potential

calcium dihydroxide (1305-62-0)	
Bioaccumulative potential	Not applicable for inorganic substances.

Quartz (SiO ₂) (14808-60-7)	
Bioaccumulative potential	Not applicable for inorganic substances.

12.4. Mobility in soil

calcium dihydroxide (1305-62-0)	
Ecology - soil	Expected to be highly mobile in soil.

Quartz (SiO ₂) (14808-60-7)	
Ecology - soil	Low mobility (soil).

12.5. Results of PBT and vPvB assessment

PROBAU Schnellzement	
PBT: not relevant – no registration required	
vPvB: not relevant – no registration required	

Component	
Cement, portland, chemicals (65997-15-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
calcium dihydroxide (1305-62-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Quartz (SiO ₂) (14808-60-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Disposal must be done according to official regulations. European waste catalogue. Do not discharge into drains or the environment. Do not dispose of with domestic waste.
Product/Packaging disposal recommendations	: Recycle or dispose of in compliance with current legislation.
European List of Waste (LoW) code	: 17 01 01 - concrete
HP Code	: HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition regulations

: This safety data sheet is for informational purposes only and does not comply with national legal requirements without reference to a national distributor. The national distributor is responsible for a legally compliant safety data sheet.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources : Supplier Safety Data Sheet.
Department issuing data : KFT Chemieservice GmbH
specification sheet: Im Leuschnerpark. 3 64347 Griesheim
Germany

Phone: +49 6155-8981-400 Fax: +49 6155 8981-500
Safety Data Sheet Service: +49 6155 8981-522

Contact person : Maximilian Gatterdam

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.

PROBAU Schnellzement

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method

KFT SDS EU 00

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.